

# AMK-ERR100 ELECTRIC REWIND HOSE REEL

## Available with 50' or 100' of hose



Electric motor can be mounted on any lower corner of the reel to nest reels and save compartment space

### SPECIFICATIONS

Roller Guide Assembly available

**AMK-ERR100 w/50' or 100' hose**

Depth: 21.0 in. (533 mm)

Width: 19.0 in. (483 mm)

Height: 21.6 in. (549 mm)

### Part Number

850600B40221

850600B40222

850600B40223

850600B40224

851200B40221

851200B40222

851200B40223

851200B40224

### Description

ERR100 with 50' hose, Red, 5' pump/reel connection hose, standard couplings

ERR100 with 50' hose, Blue, 5' pump/reel connection hose, standard couplings

ERR100 with 50' hose, Black, 5' pump/reel connection hose, standard couplings

ERR100 with 50' hose, Yellow, 5' pump/reel connection hose, standard couplings

ERR100 with 100' hose, Red, 5' pump/reel connection hose, standard couplings

ERR100 with 100' hose, Blue, 5' pump/reel connection hose, standard couplings

ERR100 with 100' hose, Black, 5' pump/reel connection hose, standard couplings

ERR100 with 100' hose, Yellow, 5' pump/reel connection hose, standard couplings

### Options

Add the Letter A to the part number for standard couplings on reel/tool hose, less pump/reel connection hoses

Add the Letter K to the part number for Female Mono Coupling on reel/tool hose, less pump/reel connection hoses

Add the Letter L to the part number for Mono Couplings on reel/tool hose and the 5' pump/reel connection hoses

### Weight (ready to use)

	w/ 50' hose	w/100' hose
ERR100 with standard couplings on reel/tool hose and 5' pump/reel connection hose	106.0 lbs.	132.0 lbs.
ERR100 with standard couplings on reel/tool hose, less pump/reel connection hose	102.0 lbs.	128.0 lbs.
ERR100 with Mono Couplings on reel/tool hose and the 5' pump/reel connection hose	107.3 lbs.	133.3 lbs.
ERR100 with Female Mono Coupling on the reel/tool hose, less pump/reel connection hose	102.9 lbs.	129.3 lbs.



**AMKUS**  
RESCUE SYSTEMS

4201 Montdale Drive  
Valparaiso, IN 46383-4098  
219-548-5000  
800-592-6587  
Fax: 219-476-1669