

SP9000 RATINGS	
Boom	9,000 lbs.
Stablilizer Leg (each)	9,000 lbs.
Winch	9,000 lbs.
Wire Rope	3/8" x 100' Steel Core
Weight	980 lbs.
Patent Number	8192135B2
CHASSIS RECOMMENDATION	
Chassis GVRW: Class 6	15,000 lbs 26,000 lbs.
Recommended Minimum Additional Cab to Axle Spacing (Carriers)	12"
Recommended Minimum Additional Cab to Axle Spacing (Wreckers)	17"
Min - Max Frame Height	32" - 38"
Min - Max Frame Width - Adjustable Mounting Base Width	33-3/4" to 34-3/4"

STANDARD FEATURES SP9000 (WITH INTEGRATED CONTROLS)

STANDARD FEATURES SP9000 (W	TIH INTEGRATED CONTROLS)
Part Number ITD4670	
9,000 lb. WARN High Speed Severe Duty Planetary Winch	Hydraulic Stabilizer Legs with Lock Valve Safety Features
3/8" x 100' Steel Core Rope	Self-Leveling Pavement Pads on Stabilizer Legs
Winch Free Spool Handle (Easy Reach / Easy Pull)	Fold Down Ground Penetrating Grousers on Stabilizer Legs
Winch Tensioner Plate	Adjustable LightBar Mount
(8) Eight Tie Back Points	Wire Routing System allows easy Wiring from Light Bar to Chassis
Tuff Coat Gloss Black Finish	Adjustable, Mounting System with Mounting Hardware
Stainless Steel Rear Panel	Center Recovery Boom Head
Wireless Remote Control for all Functions with Manual Over-rides	Outer Recovery Boom Head
Completely Plumbed and Ready for Installation	

OPTIONAL FEATURES

SP Series Swept Wing Light Bar Pylon

Stainless Steel Dress Up Package

(Adjustable Height 91" Wide)

SP Series Model-54 Adjustable Height SP-Light
Bar Pylon 54" Wide

Primer Gray, Ready for you to Paint Your
Own Color

SP Series Model-60 Adjustable Height SP-Light
Bar Pylon 60" Wide

SP Series Model-70 Adjustable Height SP-Light Bar Pylon 70" Wide

Note: Due To Constant Changes In Our Designs, Some Information May Change From Time To Time And Become Out Of Date. The Above Information Is For General Discussion Only.
For The Most Recent Specifications, Installation Procedures And The Latest Copy Of Our Operation Manual Please Consult The SP Series Operation Manual Found On This
Website.

