

258HTD*L HALO DC™

Dual Color Halo
Now Available



Two Colors
In One Light

Halo DC™ features the first “full image” dual-color warning beacon. Halo DC™ allows you to change from an amber beacon to a blue beacon with the flip of a switch. Other color combinations available.

Specs & Features:

- Dual Color Gen IV LED's (four of each color)
 - 24 customer selectable flash patterns including rotating patterns
 - S-LINK SYSTEM™ synchronizing capability with other STAR LED units
 - Extremely low current draw
 - Completely encapsulated circuit for increased weather and shock resistance
 - Lightweight polycarbonate, universal flange base:
 - 3-hole permanent mount
 - 1" pipe mount
 - Also available in vacuum magnet mount
 - Cig plug with Dual power on/off switch
 - Low voltage warning
 - Dimensions: (Short Dome): 4-3/4" tall x 6-13/32" dia.
(Tall Dome): 6-11/16" tall x 6-13/32" dia.
 - Voltage: 12-24V DC (permanent mount)
12V DC (cig plug)
 - Amp Draw: 0.7 Amps @ 12V DC, 0.35 Amps @ 24V DC
 - Lens Color: Clear
 - LED colors: Amber/Blue, Amber/Red,
Amber/White, Red/Green and Red/White
 - Approvals: Tall Dome SAE Class 1 (Amber/Blue)
Short Dome SAE Class 2 (Amber/Blue)
- Patents Pending



Model Numbers / Descriptions:

- 258HTDAL: Halo Dual Color LEDs, tall dome with dust cover
- 258HTDCL: Halo Dual Color LEDs, tall dome
- 258HTDSL: Halo Dual Color LEDs, short dome
- 258HTDALV: Halo Dual Color LEDs, tall dome with dust cover and vacuum magnet
- 258HTDCLV: Halo Dual Color LEDs, tall dome, vacuum magnet
- 258HTDSL: Halo Dual Color LEDs, short dome, vacuum magnet

